



CR Dahlia P873 Specification

- Number of LEDs: 16
- Power Consumption: 32 Watt
- Luminaire Luminous Flux: 3880 Lumens
- Luminaire Efficacy: 122.7 lm/w
- Driver Current (in 50mA steps): 600mA
- Lumen Maintenance Output (Ta = 25°C): L95 >100,000 hours
- Operating Temperature (for 100,000 hrs): -30 C to + 45C (1000mA)
- Maximum Operating Temperature: 45 C
- Weight (Total): 3.6kg
- Correlated Colour Temperature: 4000K
- Glare Rating: Up to G3
- Colour Rendering Index: >70

CR Dahlia Post Top LED Lantern

C&R Outdoor Lighting Ltd

www.crlighting.co.uk

- Optical Cover: PMMA
- Electrical Class: I or II
- Control System Input: N/A
- Surge Protection: 8kV Comm.Mode 6 kV Diff.Mode to IEC 61000-4-5; 10kV Single Pulse
- Dimming Control: N/A
- Lighting Regulation: Nema Socket
- Installation Height: 4 - 6m
- Installation: 76 Post top
- Material: High pressure die cast aluminium (housing)
- Finish: Polyester powder coat cured under heat
- Colours: Light Grey (RAL 7035)
- Ingress Protection: IP 66
- Wind Area (EPA): 0.032m



C&R Outdoor Lighting Ltd
www.crlighting.co.uk